



### SDI Single Core Double Insulated Rubber Flexible Power Cables NSGAFÖU

CONSTRUCTION	
<b>Conductors</b>	Tinned annealed copper conductors AS/NZS1125
<b>Insulation</b>	Special EPR compound, 3GI3 quality to VDE 0207 part 20
<b>Outer Jacket</b>	PCP (Polychloroprene) 5GM3 to VDE 0207 part 21
<b>Voltage</b>	1.9/3.3kV test voltage 6kV
<b>Colour</b>	Black
<b>Minimum Bending Radius</b>	4 x Diameter for fixed installations, 5 x Diameter for mobile installations

FEATURES	
Excellent Flexibility	
Flame Retardant and Submersible to 100m	
Temperature range -25°C + 110°C . For fixed instalation Lowest temperature is -40°C	
Maximum permissible short circuit temperature 250°C	
UV, Sunlight, Ozone, Oil, Resistant	
This cable is designed in accordance with DIN VDE 250 Part 602 as far as applicable	

APPLICATIONS	
Heavy-Duty flexible single core for mobile and fixed Installations	
Internal switchboard Wiring	
Sub-mains	
Electrical Traction vehicles	
Battery bank connections	
Machine & Equipment Cabling	
Stacker and reclaiming cabling	
Submersible to 100 metres	
Steelworks, cranes & hoists	
Other industrial applications	

PACKAGING	
<b>Standard Length Cable Packing</b>	100m 500m as well as cut to length 10mm <sup>2</sup> and above
<b>Standard Cable Markings</b>	Manufacturer Name, NSGAFÖU R.EP.110 3.3kV <Meter marked> <mm <sup>2</sup> >


Current-carrying capacity correction coefficients to meet changes in environments condition (rating factors according to the Standard AS/NZS 3008.1.1 2010 Table 27 as far as applicable)

C°	25	30	35	40	45	50	55	60	65	70	75
Rating Factor	1, 08	1, 06	1, 03	1	0, 97	0, 93	0, 9	0, 87	0, 83	0, 79	0, 75

**Please Note**

Please consult with your Electrician / Engineer to ensure this cable is suitable for the intended application and installation. Elcon Cables takes every precaution to ensure the information in this publication is correct but accepts no liability of any kind and reserves the right to change any detail in this catalogue without notification.

<b>NSW</b>	<b>QLD</b>	<b>VIC</b>
TEL 02 9602 4888 FAX 02 9602 4099 EMAIL salesnsw@elconcables.com.au	TEL 07 3805 6455 FAX 07 3805 6433 EMAIL salesqld@elconcables.com.au	TEL 03 9558 1044 FAX 03 9551 5844 EMAIL salesvic@elconcables.com.au
<b>WA</b>	<b>SA</b>	
TEL 08 9358 1809 FAX 08 9358 2182 EMAIL saleswa@elconcables.com.au	TEL 08 8326 4833 FAX 08 8326 4855 EMAIL salessa@elconcables.com.au	
<a href="http://www.elconcables.com.au">www.elconcables.com.au</a>		



### SDI Single Core Double Insulated Rubber Flexible Power Cables NSGAFÖU

Product Code	Nominal Area mm <sup>2</sup>	No Strands x Conductor size	Nominal Insulation Thickness mm	Nominal Sheath Thickness mm	Amps **	Max DC Resistance @20°C Ω/KM	Min OD mm	Max OD mm	Short circuit Rating kA (1s)	Mass Kg/Km
SDI1.5-3.3kV	1 x 1.5	28 / 0.26	1.3	0.8	31	13.70	5.5	7	0.2 kA	50
SDI2.5-3.3kV	1 x 2.5	45 / 0.26	1.3	0.8	42	8.21	5.9	7.5	0.33 kA	65
SDI4-3.3kV	1 x 4	51 / 0.31	1.3	0.8	55	5.09	6.4	8	0.53 kA	80
SDI6-3.3kV	1 x 6	75 / 0.31	1.3	0.8	70	3.39	7	8.6	0.79 kA	105
SDI10-3.3kV	1 x 10	77 / 0.41	1.5	0.8	99	1.95	8.2	10	1.32 kA	155
SDI16-3.3kV	1 x 16	123 / 0.41	1.5	0.8	130	1.24	9.2	11.1	2.11 kA	215
SDI25-3.3kV	1 x 25	190 / 0.41	1.8	1.0	173	0.795	11.3	13.4	3.3 kA	330
SDI35-3.3kV	1 X 35	268 / 0.41	1.8	1.0	214	0.565	12.5	14.6	4.62 kA	430
SDI50-3.3kV	1 x 50	384 / 0.41	1.8	1.0	270	0.393	14.1	16.4	6.60 kA	590
SDI70-3.3kV	1 x 70	545 / 0.41	1.8	1.0	340	0.277	15.9	18.3	9.24 kA	785
SDI95-3.3kV	1 x 95	724 / 0.41	2.2	1.0	410	0.210	18.2	20.8	12.54 kA	1030
SDI120-3.3kV	1 x 120	926 / 0.41	2.2	1.0	487	0.164	19.6	22.4	15.84 kA	1300
SDI150-3.3kV	1 x 150	1154 / 0.41	2.2	1.2	562	0.132	21.7	24.7	19.80 kA	1560
SDI185-3.3kV	1 x 185	1407 / 0.41	2.4	1.2	644	0.108	23.6	26.7	24.42 kA	1930
SDI240-3.3kV	1 x 240	1866 / 0.41	2.6	1.2	775	0.082	26.3	29.7	31.68 kA	2390
SDI300-3.3kV	1 x 300	1551 / 0.51	2.8	1.2	895	0.065	29.3	32.9	39.60 kA	3040
SDI400-3.3kV	1 x 400	1995 / 0.51	3.1	1.4	1079	0.049	32.5	36.4	52.80 kA	3960

**Please Note\*\***

Amperage ratings specified are in accordance with AS/NZS 3008.1.1.2009 Table 9.(Flexible "Spaced") @ 40°C  
Further Current ratings are available in the technical section of this catalogue.  
Derating factor may apply, refer to AS/NZS 3008.1.1.2009.

\* The Formula to calculate these values is:

$$I_{\text{Short Circuit}} = \frac{(132 \times S)}{\sqrt{T}}$$

Where: S = Cross Section (mm<sup>2</sup>)  
T = Time period of short circuit (s)

**Please Note**

Please consult with your Electrician / Engineer to ensure this cable is suitable for the intended application and installation.  
Elcon Cables takes every precaution to ensure the information in this publication is correct but accepts no liability of any kind and reserves the right to change any detail in this catalogue without notification.

<b>NSW</b>	<b>QLD</b>	<b>VIC</b>
TEL 02 9602 4888 FAX 02 9602 4099	TEL 07 3805 6455 FAX 07 3805 6433	TEL 03 9558 1044 FAX 03 9551 5844
EMAIL salesnsw@elconcables.com.au	EMAIL salesqld@elconcables.com.au	EMAIL salesvic@elconcables.com.au
<b>WA</b>		<b>SA</b>
TEL 08 9358 1809 FAX 08 9358 2182	<a href="http://www.elconcables.com.au">www.elconcables.com.au</a>	TEL 08 8326 4833 FAX 08 8326 4855
EMAIL saleswa@elconcables.com.au		EMAIL salessa@elconcables.com.au