



FODT Ordinary Duty 250/440V Single Insulated Flexible Single Core

CONSTRUCTION	
Conductors	Tinned annealed copper conductors AS/NZS1125
Insulation	PVC V90HT to AS/NZS3191/AS/NZS3808:2000
Voltage	250/440V
Colours	Red, Black, Blue, Grey, Orange, Brown, White, Pink, Violet, Yellow, (Green Yellow)

FEATURES	
RoHS COMPLIANT	
Excellent Flexibility	
UV Stabilised	
99.9% OFHC (Oxygen Free High Conductivity) Copper which does not show any brittleness	

APPLICATIONS	
Single core power for flexible and fixed applications	
Internal Switchboard Wiring	
Machine & Equipment Cabling	
Other Industrial Applications	

PACKAGING	
Standard Length Cable Packing	100m & 500m: Other lengths are available at time of manufacture
Standard Cable Markings	Manufacturer V90HT 250/440V

Product Code	Nominal Area mm ²	No Strands/ø mm	Nominal Insulation Thickness mm	Max DC Resistance @20°C mΩ/mt	Amps **	Nominal OD mm	Mass Kg/Mtr
FODT11602	1 x 0.5	16/0.20	0.60	40.10	3	2.10	0.009
FODT12402	1 x 0.75	24/0.20	0.60	26.70	7.5	2.30	0.012
FODT13202	1 x 1	32/0.20	0.60	20.00	16	2.60	0.015

Please Note**

Amperage ratings specified are in accordance with AS/NZS 3008.1.1.2009 Table 7.(Flexible "Spaced"). Further Current ratings are available in the technical section of this catalogue. Derating factor may apply, refer to AS/NZS 3008.1.1.2009.

Please Note

Please consult with your Electrician / Engineer to ensure this cable is suitable for the intended application and installation. Elcon Cables takes every precaution to ensure the information in this publication is correct but accepts no liability of any kind and reserves the right to change any detail in this catalogue without notification.

NSW	QLD	VIC
TEL 02 9602 4888 FAX 02 9602 4099 EMAIL salesnsw@elconcables.com.au	TEL 07 3805 6455 FAX 07 3805 6433 EMAIL salesqld@elconcables.com.au	TEL 03 9558 1044 FAX 03 9551 5844 EMAIL salesvic@elconcables.com.au
WA	SA	
TEL 08 9358 1809 FAX 08 9358 2182 EMAIL saleswa@elconcables.com.au	TEL 08 8326 4833 FAX 08 8326 4855 EMAIL salessa@elconcables.com.au	
www.elconcables.com.au		