



Figure 8 and twisted Shot fire Cable

CONSTRUCTION	
Conductors	Tinned or Plain Copper Wire Class 2
Insulation	PVC V90
Rated Voltage	E.L.V
Colour Code	
EFT21071 - Figure 8	White & Red
ETT21061 - Twisted	Green & Red

FEATURES
99.9% Oxygen Free Copper
Tinned Copper
Temperature range -25°C to +90°C
RoHS Compliant
UV Stabilised

APPLICATIONS
Intercomms
Connection Of Explosive Devices

PACKAGING	
Standard Length Cable Packing	500m

Code	Nominal Conductor mm ²	Stranding	Average Insulation Thickness	Nominal OD mm	Max DC Resistance mΩ/mt	Mass kg/100mt
EFT21071 (TCW Figure 8)	0.4	1/0.71	0.50	1.70 x 3.50	45.30	1.25
ETT21061 (PCW Twisted Pair)	0.4	1/0.71	0.40	3.00	46.20	1.03

** NOT FOR MAINS CONNECTION

Please Note

Please consult with your Electrician / Engineer to ensure this cable is suitable for the intended application and installation. Elcon Cables takes every precaution to ensure the information in this publication is correct but accepts no liability of any kind and reserves the right to change any detail in this catalogue without notification.

NSW	QLD	VIC
TEL 02 9602 4888 FAX 02 9602 4099 EMAIL salesnsw@elconcables.com.au	TEL 07 3805 6455 FAX 07 3805 6433 EMAIL salesqld@elconcables.com.au	TEL 03 9558 1044 FAX 03 9551 5844 EMAIL salesvic@elconcables.com.au
WA	SA	
TEL 08 9358 1809 FAX 08 9358 2182 EMAIL saleswa@elconcables.com.au	TEL 08 8326 4833 FAX 08 8326 4855 EMAIL salessa@elconcables.com.au	
www.elconcables.com.au		