



Data Cables Pairs Overall Screen

CONSTRUCTION	
Conductors	Tinned Annealed Copper Wire Class 2
Insulation	Foam PE
Drain	7/0.20 Tinned Copper Wire
Overall Screen	Aluminium Tape (100% Coverage)
Sheath	V75 PVC Grey
Rated Voltage	Maximum working voltage 300V RMS** Not suitable for mains connection
Voltage Test	Core to Core 1.5kV AC/1min Core to Screen 1.5kV AC/1min
Core Colours	
1 Pair	White & Blue
2 Pair	White & Blue, White & Orange
4 Pair	White & Blue, White & Orange, White & Green, White & Brown

FEATURES	
Mtr Marked	
RoHS Compliant	

APPLICATIONS	
Internal and external inter-connections of electronic apparatus such as computers, intercoms, telemetering, signaling and alarm systems.	

PACKAGING	
Standard Length Cable Packing	100m & 500m
Standard Cable Marking	Elcon Cables, Part No, Abbreviated Description V75 not for mains connection <Meter marked> <Year of Manufacturer>

Code	Nominal Conductor mm ²	Stranding	Bending Radius mm	Core Nominal OD mm	Cable Nominal OD mm	Conductor Resistance Ω/100mt
DPS1P0.22S	0.22	7/0.20	44	1.2	4.4	8.90
DPS2P0.22S	0.22	7/0.20	56	1.2	5.6	8.90
DPS4P0.22S	0.22	7/0.20	62	1.2	6.2	8.90

** NOT FOR MAINS CONNECTION

Please Note

Please consult with your Electrician / Engineer to ensure this cable is suitable for the intended application and installation.

Elcon Cables takes every precaution to ensure the information in this publication is correct but accepts no liability of any kind and reserves the right to change any detail in this catalogue without notification.

NSW	QLD	VIC
TEL 02 9602 4888 FAX 02 9602 4099	TEL 07 3805 6455 FAX 07 3805 6433	TEL 03 9558 1044 FAX 03 9551 5844
EMAIL salesnsw@elconcables.com.au	EMAIL salesqld@elconcables.com.au	EMAIL salesvic@elconcables.com.au
WA	SA	
TEL 08 9358 1809 FAX 08 9358 2182	TEL 08 8326 4833 FAX 08 8326 4855	
EMAIL saleswa@elconcables.com.au	EMAIL salessa@elconcables.com.au	
www.elconcables.com.au		